


stafstaal

platbulb (Holland-profiel of HP)

leveringsvoorwaarden: –
 toleranties: NEN-EN 10067
 max. handelslengte: 12 m



b x t mm	G ₈ kg/m	A mm ²	c mm	A _L m ² /m	I _z x10 ⁴ mm ⁴	W _{z,el} x10 ³ mm ³
80 x 6	4,97	621	14	0,191	38,7	8,10
80 x 7	5,60	700	14	0,194	43,3	9,24
100 x 6	6,20	775	15,5	0,234	76,2	12,7
100 x 7	6,99	874	15,5	0,236	85,3	14,5
100 x 8	7,79	974	15,5	0,238	94,3	16,3
120 x 6	7,32	932	17	0,276	133	18,5
120 x 7	8,26	1052	17	0,278	149	21,0
120 x 8	9,20	1172	17	0,280	165	23,6
140 x 7	9,94	1243	19	0,320	241	29,0
140 x 8	11,1	1383	19	0,322	266	32,5
140 x 9	12,2	1523	19	0,324	291	36,0
160 x 7	11,7	1460	22	0,365	373	38,6
160 x 8	13,0	1620	22	0,367	411	43,3
160 x 9	14,2	1780	22	0,369	449	47,9
180 x 8	15,1	1886	25	0,411	609	55,9
180 x 9	16,5	2066	25	0,413	664	61,8
180 x 10	18,0	2246	25	0,415	717	67,7
200 x 9	18,9	2366	28	0,457	942	77,7
200 x 10	20,5	2566	28	0,459	1017	85,1
200 x 11,5	22,9	2860	28	0,462	1126	96,2
220 x 10	23,2	2900	31	0,503	1396	105
220 x 11,5	25,8	3230	31	0,506	1550	118
220 x 12	26,7	3340	31	0,507	1595	122
240 x 10	26,0	3249	34	0,547	1865	126
240 x 12	29,8	3729	34	0,551	2127	148
260 x 11	31,0	3871	37	0,593	2605	163
260 x 12	33,0	4131	37	0,596	2774	175
280 x 11	34,1	4268	40	0,637	3333	191
280 x 12	36,4	4548	40	0,639	3647	211
300 x 11	37,4	4678	43	0,681	4192	222
300 x 12	39,8	4979	43	0,683	4459	239
320 x 12	43,4	5425	46	0,728	5525	275
320 x 14	48,7	6085	46	0,732	6168	313

stripstaal

(b > 150 mm)

leveringsvoorwaarden: NEN-EN 10025-1 en -2
 toleranties: DIN 59200
 max. handelslengte: 6 m



b x t mm	G ₈ kg/m	A mm ²	A _L m ² /m	b x t mm	G ₈ kg/m	A mm ²	A _L m ² /m
160 x 5	6,40	800	0,330	180 x 20	28,8	3600	0,400
160 x 6	7,68	960	0,332	180 x 25	36,0	4500	0,410
160 x 8	10,2	1280	0,336	180 x 30	43,2	5400	0,420
160 x 10	12,8	1600	0,340	180 x 40	57,6	7200	0,440
160 x 12	15,4	1920	0,344	180 x 50	72,0	9000	0,460
160 x 15	19,2	2400	0,350	200 x 5	8,00	1000	0,410
160 x 20	25,6	3200	0,360	200 x 6	9,60	1200	0,412
160 x 25	32,0	4000	0,370	200 x 8	12,8	1600	0,416
160 x 30	38,4	4800	0,380	200 x 10	16,0	2000	0,420
165 x 5	6,60	825	0,340	200 x 12	19,2	2400	0,424
165 x 6	7,92	990	0,342	200 x 15	24,0	3000	0,430
165 x 8	10,6	1320	0,346	200 x 20	32,0	4000	0,440
165 x 10	13,2	1650	0,350	200 x 25	40,0	5000	0,450
165 x 12	15,8	1980	0,354	200 x 30	48,0	6000	0,460
165 x 15	19,8	2475	0,360	200 x 40	64,0	8000	0,480
165 x 20	26,4	3300	0,370	200 x 50	80,0	10000	0,500
165 x 25	33,0	4125	0,380	220 x 6	10,6	1320	0,452
165 x 30	39,6	4950	0,390	220 x 8	14,1	1760	0,456
170 x 5	6,80	850	0,350	220 x 10	17,6	2200	0,460
170 x 6	8,16	1020	0,352	220 x 12	21,1	2640	0,464
170 x 8	10,9	1360	0,356	220 x 15	26,4	3300	0,470
170 x 10	13,6	1700	0,360	220 x 20	35,2	4400	0,480
170 x 12	16,3	2040	0,364	220 x 25	44,0	5500	0,490
170 x 15	20,4	2550	0,370	220 x 30	52,8	6600	0,500
170 x 20	27,2	3400	0,380	230 x 6	11,0	1380	0,472
180 x 5	7,20	900	0,370	230 x 8	14,7	1840	0,476
180 x 6	8,64	1080	0,372	230 x 10	18,4	2300	0,480
180 x 8	11,5	1440	0,376	230 x 12	22,1	2760	0,484
180 x 10	14,4	1800	0,380	230 x 15	27,6	3450	0,490
180 x 12	17,3	2160	0,384	230 x 20	36,8	4600	0,500
180 x 15	21,6	2700	0,390	230 x 25	46,0	5750	0,510


stripstaal

(b > 150 mm)

leveringsvoorwaarden: NEN-EN 10025-1 en -2

toleranties: DIN 59200

max. handelslengte: 6 m




b x t mm	G _B kg/m	A mm ²	A _L m ² /m	b x t mm	G _B kg/m	A mm ²	A _L m ² /m
230 x 30	55,2	6900	0,520	300 x 30	72,0	9000	0,660
240 x 10	19,2	2400	0,500	300 x 40	96,0	12000	0,680
240 x 12	23,0	2880	0,504	300 x 50	120,0	15000	0,700
240 x 15	28,8	3600	0,510	350 x 6	16,8	2100	0,712
240 x 20	38,4	4800	0,520	350 x 8	22,4	2800	0,716
250 x 5	10,0	1250	0,510	350 x 10	28,0	3500	0,720
250 x 6	12,0	1500	0,512	350 x 12	33,6	4200	0,724
250 x 8	16,0	2000	0,516	350 x 15	42,0	5250	0,730
250 x 10	20,0	2500	0,520	350 x 20	56,0	7000	0,740
250 x 12	24,0	3000	0,524	350 x 25	70,0	8750	0,750
250 x 15	30,0	3750	0,530	350 x 30	84,0	10500	0,760
250 x 20	40,0	5000	0,540	400 x 6	19,2	2400	0,812
250 x 25	50,0	6250	0,550	400 x 8	25,6	3200	0,816
250 x 30	60,0	7500	0,560	400 x 10	32,0	4000	0,820
250 x 40	80,0	10000	0,580	400 x 12	38,4	4800	0,824
280 x 6	13,4	1680	0,572	400 x 15	48,0	6000	0,830
280 x 8	17,9	2240	0,576	400 x 20	64,0	8000	0,840
280 x 10	22,4	2800	0,580	400 x 25	80,0	10000	0,850
280 x 12	26,9	3360	0,584	400 x 30	96,0	12000	0,860
280 x 15	33,6	4200	0,590	400 x 40	128,0	16000	0,880
280 x 20	44,8	5600	0,600	400 x 50	160,0	20000	0,900
280 x 25	56,0	7000	0,610	500 x 8	32,0	4000	1,02
280 x 30	67,2	8400	0,620	500 x 10	40,0	5000	1,02
300 x 5	12,0	1500	0,610	500 x 12	48,0	6000	1,02
300 x 6	14,4	1800	0,612	500 x 15	60,0	7500	1,03
300 x 8	19,2	2400	0,616	500 x 20	80,0	10000	1,04
300 x 10	24,0	3000	0,620	500 x 25	100,0	12500	1,05
300 x 12	28,8	3600	0,624	500 x 30	120,0	15000	1,06
300 x 15	36,0	4500	0,630	500 x 40	160,0	20000	1,08
300 x 20	48,0	6000	0,640	500 x 50	200,0	25000	1,10
300 x 25	60,0	7500	0,650				

platen

koudgewalst, onbehandeld (licht geolied)

leveringsvoorwaarden: NEN-EN 10130

toleranties: NEN-EN 10131



t mm	G _B (kg/plaat)			
	ℓ x b	2000 x 1000	2500 x 1250	3000 x 1500
0,50		8,00	12,5	
0,60		9,60		
0,70		11,2		
0,75		12,0	18,8	27,0
0,80		12,8		
0,90		14,4	22,5	
1,00		16,0	25,0	36,0
1,25		20,0	31,3	45,0
1,50		24,0	37,5	54,0
2,00		32,0	50,0	72,0
2,50		40,0	62,5	90,0
3,00		48,0	75,0	108